



Application Asset

Astra Automation

NetApp
June 28, 2024

目录

Application Asset	1
Application Asset overview	1
List the application assets for an application backup	1
Retrieve an application asset from an application backup	10
List the application assets for a managed cluster	20
Retrieve an application asset for a managed cluster	29
List the application assets for an app	39
Retrieve an application asset for an app	48
List the application assets from an application backup for an app	58
Retrieve an application asset from an application backup for an app	67
List application assets for an application snapshot	77
Retrieve an application asset for an application snapshot and app	86

Application Asset

Application Asset overview

The Application Asset API provides access to internal collections of state information used to manage applications.

List the application assets for an application backup

GET /accounts/{account_id}/topology/v1/appBackups/{appBackup_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
appBackup_id	string	path	True	ID of the containing appBackup resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: assetType,asset Name

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset from an application backup

GET

/accounts/{account_id}/topology/v1/appBackups/{appBackup_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
appBackup_id	string	path	True	ID of the containing appBackup resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	<p>JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	<p>JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	<p>JSON string containing an identifier assigned by Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	<p>JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the application assets for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/apps/{app_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
app_id	string	path	True	ID of the containing app resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: assetType,asset Name
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^[a-z0-9A-Z_-]{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/apps/{app_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
app_id	string	path	True	ID of the containing app resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	<p>JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	<p>JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	<p>JSON object containing a Kubernetes group/version/kind.</p>
resource	type_json	False	<p>JSON object containing the entire content of the Kubernetes resource definition.</p>
assetID	string	True	<p>JSON string containing an identifier assigned by Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	<p>JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-.]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-.]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the application assets for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>assetType,assetName</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-.]{1,63})\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-.]{1,63}}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	<p>JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	<p>JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	<p>JSON string containing an identifier assigned by Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	<p>JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-.]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-.]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the application assets from an application backup for an app

GET

/accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups/{appBackup_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
appBackup_id	string	path	True	ID of the containing appBackup resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: assetType,asset Name

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-.]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-.]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset from an application backup for an app

GET

/accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups/{appBackup_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appBackup_id	string	path	True	ID of the containing appBackup resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	<p>JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	<p>JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	<p>JSON string containing an identifier assigned by Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	<p>JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-.]{1,63})\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^[a-z0-9A-Z_-.]{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List application assets for an application snapshot

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps/{appSnap_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the containing appSnap resource
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>assetType,assetName</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset for an application snapshot and app

GET

/accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps/{appSnap_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the containing appSnap resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

版权信息

版权所有 © 2024 NetApp, Inc.。保留所有权利。中国印刷。未经版权所有者事先书面许可，本档中受版权保护的任何部分不得以任何形式或通过任何手段（图片、电子或机械方式，包括影印、录音、录像或存储在电子检索系统中）进行复制。

从受版权保护的 NetApp 资料派生的软件受以下许可和免责声明的约束：

本软件由 NetApp 按“原样”提供，不含任何明示或暗示担保，包括但不限于适销性以及针对特定用途的适用性的隐含担保，特此声明不承担任何责任。在任何情况下，对于因使用本软件而以任何方式造成的任何直接性、间接性、偶然性、特殊性、惩罚性或后果性损失（包括但不限于购买替代商品或服务；使用、数据或利润方面的损失；或者业务中断），无论原因如何以及基于何种责任理论，无论出于合同、严格责任或侵权行为（包括疏忽或其他行为），NetApp 均不承担责任，即使已被告知存在上述损失的可能性。

NetApp 保留在不另行通知的情况下随时对本文档所述的任何产品进行更改的权利。除非 NetApp 以书面形式明确同意，否则 NetApp 不承担因使用本文档所述产品而产生的任何责任或义务。使用或购买本产品不表示获得 NetApp 的任何专利权、商标权或任何其他知识产权许可。

本手册中描述的产品可能受一项或多项美国专利、外国专利或正在申请的专利的保护。

有限权利说明：政府使用、复制或公开本文档受 DFARS 252.227-7013（2014 年 2 月）和 FAR 52.227-19（2007 年 12 月）中“技术数据权利 — 非商用”条款第 (b)(3) 条规定的限制条件的约束。

本文档中所含数据与商业产品和/或商业服务（定义见 FAR 2.101）相关，属于 NetApp, Inc. 的专有信息。根据本协议提供的所有 NetApp 技术数据和计算机软件具有商业性质，并完全由私人出资开发。美国政府对这些数据的使用权具有非排他性、全球性、受限且不可撤销的许可，该许可既不可转让，也不可再许可，但仅限在与交付数据所依据的美国政府合同有关且受合同支持的情况下使用。除本文档规定的情形外，未经 NetApp, Inc. 事先书面批准，不得使用、披露、复制、修改、操作或显示这些数据。美国政府对国防部的授权仅限于 DFARS 的第 252.227-7015(b)（2014 年 2 月）条款中明确的权利。

商标信息

NetApp、NetApp 标识和 <http://www.netapp.com/TM> 上所列的商标是 NetApp, Inc. 的商标。其他公司和产品名称可能是其各自所有者的商标。