



LDAP User

Astra Automation

NetApp
December 01, 2023

目录

LDAP User	1
LDAP User overview	1
List all LDAP users	1
Retrieve an LDAP user	9

LDAP User

LDAP User overview

The LDAP User API provides read-only access to LDAP users within the configured LDAP server.

List all LDAP users

GET /accounts/{account_id}/core/v1/ldapUsers

Returns a JSON array of JSON objects containing the results of the request URL.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,cn,dn
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
continue		query	False	<p>Indicates the token to resume listing from.</p> <p>URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue></p> <p>OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue>&lt;/continue&gt;"</p>

Response

Status: 200, Returns a JSON array of JSON objects containing the results of the request URL.

Name	Type	Required	Description
items	array[Any of: ldapUser_1.0_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-ldapUsers",
  "version": "1.0",
  "items": [
    [
      "b4bcef18-14ad-5bc1-91ce-3cce15aa8791",
      "John Doe",
      "cn=John Doe,ou=people,dc=example,dc=com"
    ],
    [
      "98b10d6f-8693-555f-b258-70de4cc7301f",
      "Jane Doe",
      "cn=Jane Doe,ou=people,dc=example,dc=com"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/14",
  "title": "Unauthorized access",
  "detail": "The user isn't enabled.",
  "status": "403"
}
```

Response

Status: 406, Not acceptable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/32",
  "title": "Unsupported content type",
  "detail": "The response can't be returned in the requested format.",
  "status": "406"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example error response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

ldapUser_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-ldapUser"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
email	string	False	JSON string representing the email of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 63
firstName	string	False	JSON string representing the first name of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
lastName	string	False	JSON string representing the last name of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
cn	string	False	JSON string representing the LDAP group name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
dn	string	False	JSON string representing the distinguished name of the LDAP group. Defined values are: <ul style="list-style-type: none"> • Conforms to RFC 4514

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an LDAP user

GET /accounts/{account_id}/core/v1/ldapUsers/{ldapUser_id}

Returns a JSON object representing the stored LDAP resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
ldapUser_id	string	path	True	ID of the ldapUser collection to list

Response

Status: 200, Returns a JSON object representing the stored LDAP resource.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-ldapUser"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
email	string	False	JSON string representing the email of the LDAP user. Defined values are: <ul style="list-style-type: none"> Minimum length: 3 Maximum length: 63

Name	Type	Required	Description
firstName	string	False	JSON string representing the first name of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
lastName	string	False	JSON string representing the last name of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
cn	string	False	JSON string representing the LDAP group name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
dn	string	False	JSON string representing the distinguished name of the LDAP group. Defined values are: <ul style="list-style-type: none"> • Conforms to RFC 4514
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-ldapUser",
  "version": "1.0",
  "id": "2add73ff-89dc-5ff1-be85-39d97549556d",
  "email": "<a href="
mailto:johndoe@example.com">johndoe@example.com</a>",
  "firstName": "John",
  "lastName": "Doe",
  "cn": "John Doe",
  "dn": "cn=John Doe,ou=people,dc=example,dc=com",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

版权信息

版权所有 © 2023 NetApp, Inc.。保留所有权利。中国印刷。未经版权所有者事先书面许可，本档中受版权保护的任何部分不得以任何形式或通过任何手段（图片、电子或机械方式，包括影印、录音、录像或存储在电子检索系统中）进行复制。

从受版权保护的 NetApp 资料派生的软件受以下许可和免责声明的约束：

本软件由 NetApp 按“原样”提供，不含任何明示或暗示担保，包括但不限于适销性以及针对特定用途的适用性的隐含担保，特此声明不承担任何责任。在任何情况下，对于因使用本软件而以任何方式造成的任何直接性、间接性、偶然性、特殊性、惩罚性或后果性损失（包括但不限于购买替代商品或服务；使用、数据或利润方面的损失；或者业务中断），无论原因如何以及基于何种责任理论，无论出于合同、严格责任或侵权行为（包括疏忽或其他行为），NetApp 均不承担责任，即使已被告知存在上述损失的可能性。

NetApp 保留在不另行通知的情况下随时对本文档所述的任何产品进行更改的权利。除非 NetApp 以书面形式明确同意，否则 NetApp 不承担因使用本文档所述产品而产生的任何责任或义务。使用或购买本产品不表示获得 NetApp 的任何专利权、商标权或任何其他知识产权许可。

本手册中描述的产品可能受一项或多项美国专利、外国专利或正在申请的专利的保护。

有限权利说明：政府使用、复制或公开本文档受 DFARS 252.227-7013（2014 年 2 月）和 FAR 52.227-19（2007 年 12 月）中“技术数据权利 — 非商用”条款第 (b)(3) 条规定的限制条件的约束。

本文档中所含数据与商业产品和/或商业服务（定义见 FAR 2.101）相关，属于 NetApp, Inc. 的专有信息。根据本协议提供的所有 NetApp 技术数据和计算机软件具有商业性质，并完全由私人出资开发。美国政府对这些数据的使用权具有非排他性、全球性、受限且不可撤销的许可，该许可既不可转让，也不可再许可，但仅限在与交付数据所依据的美国政府合同有关且受合同支持的情况下使用。除本文档规定的情形外，未经 NetApp, Inc. 事先书面批准，不得使用、披露、复制、修改、操作或显示这些数据。美国政府对国防部的授权仅限于 DFARS 的第 252.227-7015(b)（2014 年 2 月）条款中明确的权利。

商标信息

NetApp、NetApp 标识和 <http://www.netapp.com/TM> 上所列的商标是 NetApp, Inc. 的商标。其他公司和产品名称可能是其各自所有者的商标。