



Application Snapshot

Astra Automation

NetApp
December 01, 2023

This PDF was generated from https://docs.netapp.com/zh-tw/astra-automation-2211/reference/application_snapshot_overview.html on December 01, 2023. Always check docs.netapp.com for the latest.

目錄

Application Snapshot	1
Application Snapshot overview	1
Create a new application snapshot for an app	1
List the application snapshots for an app	11
Retrieve an application snapshot	21
Delete an application snapshot	28

Application Snapshot

Application Snapshot overview

The Application Snapshot API provides CRUD (Create-Read-Update-Delete) access to appSnap resources to create and view snapshots of a managed application.

Create a new application snapshot for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps

Indicates the desired values for the Application Snapshot API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource

Request Body

Indicates the desired values for the Application Snapshot API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appSnap"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"

Name	Type	Required	Description
name	string	False	<p>JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system will assign a name for the snapshot. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
metadata	type_astra_metadata	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels.

Example request

```
{
  "type": "application/astra-appSnap",
  "version": "1.1",
  "name": "app-name-245"
}
```

Response

Status: 201, Returns the newly created appSnap resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-appSnap"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system will assign a name for the snapshot. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
scheduleID	string	False	JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and which schedule triggered the snapshot. Only present for snapshots initiated by a schedule. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotAppAsset	string	False	<p>JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed". Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application snapshot is scheduled for discovery • "discovering" - The application snapshot is in the process of being discovered • "running" - The application snapshot is running normally • "completed" - The application snapshot has completed • "failed" - The application snapshot is in a permanent failure state • "removed" - The application snapshot is not currently accessible • "unknown" - The application snapshot state cannot be determined

Name	Type	Required	Description
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDetails]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-appSnap",
  "version": "1.1",
  "id": "ab41abde-ae1b-5361-ae00-d82deac97bf3",
  "name": "app-name-245",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```


Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	False	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

type_astra_stateDetails

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field

Name	Type	Required	Description
reason	string	True	Reason why the request body field is invalid

List the application snapshots for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: id,name,state

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appSnap_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appSnaps",
  "version": "1.1",
  "items": [
    [
      "2b6dafc3-2172-4431-a482-6306b2703130",
      "app-name-245",
      "pending"
    ],
    [
      "6fd9b31a-3924-4c9a-878b-175fa9538b8c",
      "app-name-244",
      "completed"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetails

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appSnap_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-appSnap"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system will assign a name for the snapshot. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
scheduleID	string	False	JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and which schedule triggered the snapshot. Only present for snapshots initiated by a schedule. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
snapshotAppAsset	string	False	JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed". Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application snapshot is scheduled for discovery • "discovering" - The application snapshot is in the process of being discovered • "running" - The application snapshot is running normally • "completed" - The application snapshot has completed • "failed" - The application snapshot is in a permanent failure state • "removed" - The application snapshot is not currently accessible • "unknown" - The application snapshot state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> "failed" - One or more execution hooks have failed "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDetails]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> Minimum items: 0
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application snapshot

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps/{appSnap_id}

Returns the stored Application Snapshot API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the appSnap collection to list

Response

Status: 200, Returns the stored Application Snapshot API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-appSnap"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system will assign a name for the snapshot. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
scheduleID	string	False	JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and which schedule triggered the snapshot. Only present for snapshots initiated by a schedule. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotAppAsset	string	False	<p>JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed". Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application snapshot is scheduled for discovery • "discovering" - The application snapshot is in the process of being discovered • "running" - The application snapshot is running normally • "completed" - The application snapshot has completed • "failed" - The application snapshot is in a permanent failure state • "removed" - The application snapshot is not currently accessible • "unknown" - The application snapshot state cannot be determined

Name	Type	Required	Description
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDetails]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-appSnap",
  "version": "1.1",
  "id": "ab41abde-ae1b-5361-ae00-d82deac97bf3",
  "name": "app-name-245",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetails

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete an application snapshot

DELETE /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps/{appSnap_id}

Removes the specified Application Snapshot API resource.

Side Effects

- If a snapshot is in progress, the snapshot is cancelled.
- If a snapshot is complete, the snapshot data is deleted.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the appSnap collection to list

Response

Status: 204, Indicates if the appSnap resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/144",
  "title": "Backup in progress",
  "detail": "The snapshot wasn't deleted because it is currently being
used by a backup.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

版權資訊

Copyright © 2023 NetApp, Inc. 版權所有。台灣印製。非經版權所有人事先書面同意，不得將本受版權保護文件的任何部分以任何形式或任何方法（圖形、電子或機械）重製，包括影印、錄影、錄音或儲存至電子檢索系統中。

由 NetApp 版權資料衍伸之軟體必須遵守下列授權和免責聲明：

此軟體以 NETAPP「原樣」提供，不含任何明示或暗示的擔保，包括但不限於有關適售性或特定目的適用性之擔保，特此聲明。於任何情況下，就任何已造成或基於任何理論上責任之直接性、間接性、附隨性、特殊性、懲罰性或衍生性損害（包括但不限於替代商品或服務之採購；使用、資料或利潤上的損失；或企業營運中斷），無論是在使用此軟體時以任何方式所產生的契約、嚴格責任或侵權行為（包括疏忽或其他）等方面，NetApp 概不負責，即使已被告知有前述損害存在之可能性亦然。

NetApp 保留隨時變更本文所述之任何產品的權利，恕不另行通知。NetApp 不承擔因使用本文所述之產品而產生的責任或義務，除非明確經過 NetApp 書面同意。使用或購買此產品並不會在依據任何專利權、商標權或任何其他 NetApp 智慧財產權的情況下轉讓授權。

本手冊所述之產品受到一項（含）以上的美國專利、國外專利或申請中專利所保障。

有限權利說明：政府機關的使用、複製或公開揭露須受 DFARS 252.227-7013（2014 年 2 月）和 FAR 52.227-19（2007 年 12 月）中的「技術資料權利 - 非商業項目」條款 (b)(3) 小段所述之限制。

此處所含屬於商業產品和 / 或商業服務（如 FAR 2.101 所定義）的資料均為 NetApp, Inc. 所有。根據本協議提供的所有 NetApp 技術資料和電腦軟體皆屬於商業性質，並且完全由私人出資開發。美國政府對於該資料具有非專屬、非轉讓、非轉授權、全球性、有限且不可撤銷的使用權限，僅限於美國政府為傳輸此資料所訂合約所允許之範圍，並基於履行該合約之目的方可使用。除非本文另有規定，否則未經 NetApp Inc. 事前書面許可，不得逕行使用、揭露、重製、修改、履行或展示該資料。美國政府授予國防部之許可權利，僅適用於 DFARS 條款 252.227-7015(b)（2014 年 2 月）所述權利。

商標資訊

NETAPP、NETAPP 標誌及 <http://www.netapp.com/TM> 所列之標章均為 NetApp, Inc. 的商標。文中所涉及的所有其他公司或產品名稱，均為其各自所有者的商標，不得侵犯。